



Molex Incorporated
PSR 0339

1

Amendment of June 4, 2008
03MO 0422USP

Claims

1. (new)

5 | An optical connector (1) for establishing multimedia-
connections in a motor vehicle, comprising:
a dielectric connector housing forming a
receptacle for mating connection with a complementary
connector, said receptacle of said dielectric housing
10 | being formed by sidewalls and a rear wall of said housing,
said rear wall having openings in it,
at least an optical connection element
including an optical fiber section in said connector
housing, arranged in said receptacle, for mating
15 | connection with a complementary optical connection element
of the complementary connector,
at least an electro-optical component including
electronic circuits and being arranged on a rear side of
said rear wall opposite to said receptacle, and
20 | ESD protection means (30) comprising:
at least one discharge section projecting
towards the receptacle and having a free end, being
exposed to the interior of the receptacle, to provide an
25 | ESD protection within the receptacle, and
at least one
electrically conductive discharge finger, penetrating
said rear wall through said opening and terminating in
said discharge section,
30 | wherein said discharge section (34, 36, 38) is
arranged in the vicinity of the optical connection element

Deleted: o

Deleted: , in particular

Deleted: according to the
MOST-standard

Deleted: (40) with

Deleted: (50)

Deleted: (94, 96)

Deleted: (40) and

Deleted: (54, 56) with

Deleted: wherein said ESD
protection means (30)
comprises

Deleted: (34, 36, 38)

Deleted: (34a, 36a, 38a)

Deleted: (50)

Deleted: (50)

Deleted: 2. Optical connector
(1) according to Claim 1,
wherein the ESD protection
means (30) comprises an

Deleted: (64, 66, 68)

Deleted: (34, 36, 38) and the

in such a way that the discharge finger forms a lightning arrester for protection of the optical connection element.

Deleted: (94, 96)

Deleted: (64, 66, 68)

Deleted: (94, 96)

2. (new)

The optical connector according to claim 1, also including an U-shaped shielding clamp that has at least one discharge section having a front edge, wherein said at least one discharge section of said ESD protection means also has a front edge, all said front edges running flush in a lateral plane that is set back with regard to front sides of said optical fiber section.

3. (claim 8 amended)

The optical connector according to claim 1 wherein the ESD protection means comprises a plurality of discharge fingers with said discharge sections thereon.

4. (claim 3 amended)

The optical connector, according to claim 3, wherein the free ends of the discharge sections extend essentially parallel to the introduction direction of the complementary connector.

Deleted: o

Deleted: (1)

Deleted: 1 or 2

Deleted: (34, 36, 38)

Deleted: s

Deleted: (E)

5. (claim 4 amended)

The optical connector, according to claim 4,
wherein the receptacle includes a single cavity, having,
at a front side, an opening for introducing the
complementary connector and
at said rear wall, a pair of optical connection
elements.

6. (claim 9 amended)

The optical connector, according to claim 5,
wherein the ESD protection means, has, a first and a
second discharge sections including first and second
conductive fingers, extend transversely with respect to
the introduction direction, of the complementary
connector, and a third discharge section which is arranged
between said pair of optical connection elements,
and
wherein, said conductive fingers, are assigned to a
pair of electro-optical components.

7. (claim 11 amended)

Deleted: o

Deleted: (1)

Deleted: one of

Deleted: s

Deleted: 2 or 3

Deleted: (49)

Deleted: wherein the
discharge finger (64, 66,
68) is arranged

Deleted: a

Deleted: side of the cavity
(49) opposite to the front
side

Deleted: ¶

5. Optical connector (1)
according to one of the
preceding claims,
wherein the cavity (49) is
bounded by a rear wall
(40b) at its rear side and
the ESD protection means
(30) penetrates the rear
wall (40b). ¶

¶
6. Optical connector (1)
according to one of the
preceding claims,
wherein the ESD protection
means (30) comprises an
electrically conductive
discharge finger (64, 66,
68) terminating in said
discharge section (34, 36,
38) and the rear wall (40b). ¶ [1]

Deleted: 7. Optical conn [2]

Deleted: o

Deleted: (1)

Deleted: one of the preceding

Deleted: s

Deleted: (30)

Deleted: at least

Deleted: (64, 66) with i [3]

Deleted: ing

Deleted: (E)

Deleted: wherein said [4]

Deleted: the arm section [5]

Deleted: (64, 66)

Deleted: the first and second

Deleted: , respectively

Deleted: 10. Optical [6]

The optical connector, according to claim 6,
wherein the conductive fingers extend along a front side
of the pair of electro-optical components.

8. (claim 12 amended)

Deleted: o

Deleted: (1)

Deleted: 9 or 10

Deleted: arm sections of the
first and second discharge

Deleted: (64, 66)

Deleted: first and second

Deleted: , respectively

Deleted: ¶

Deleted: o

Deleted: (1)

Deleted: one of

Deleted: s 9 to 11

Deleted: first and second
discharge

Deleted: (B)

The optical connector, according to claim 6

wherein the conductive fingers are offset transversely
with respect to the introduction direction.

9. (claim 13 amended)

Deleted: o

Deleted: (1)

Deleted: one of

Deleted: s 9 to 12

Deleted: discharge

Deleted: (64, 66)

The optical connector, according to claim 8

wherein the first and second conductive fingers are
formed asymmetrically.

10. (claim 14 amended)

The optical connector, according to claim 5,
wherein the ESD protection means has discharge
conductive fingers, each having a discharge section,
wherein the first optical connection element of said
pair is arranged between a first and a third of the
discharge sections,
wherein the second optical connection element of said
pair is arranged between a second and the third of the
discharge sections, and
wherein the third discharge section is arranged
between the first and second optical connection elements
of said pair.

11. (claim 15 amended)

The optical connector, according to claim 10,
wherein the receptacle has a cavity, the cavity has
at a front side an opening for introducing the
complementary connector, the cavity is bounded by said
rear wall, at a rear side opposite to the front side, and
the rear wall has at least three openings through which
the respective discharge sections extend.

12. (claim 16 amended)

The optical connector, according to claim 10,
wherein the discharge sections are stamped and formed
from sheet metal at the ends of integral fingers.

Deleted: o

Deleted: (1)

Deleted: one of the preceding

Deleted: s

Deleted: wherein said optical connection element (94, 96) is a first optical connection element (94, 96) and the connector has at least a second optical connection element (94, 96) for mating connection with a further complementary optical connection element of the complementary connector.

Deleted: (30)

Deleted: at least three

Deleted: (64, 66, 68) with in

Deleted: case

Deleted: (34, 36, 38)

Deleted: (34, 38)

Deleted: (36, 38)

Deleted: (38)

Deleted: o

Deleted: (1)

Deleted: 14

Deleted: (49)

Deleted: (49)

Deleted: (49)

Deleted: a

Deleted: (40b)

Deleted: (40b)

Deleted: in each case one of

Deleted: s

Deleted: f

Deleted: o

Deleted: (1)

Deleted: 14 or 15

Deleted: first, second and third

Deleted: fingers

Deleted: in one piece

13. (claim 17 amended)

5 | The optical connector, according to claim 1,
| wherein the ESD protection means has a dedicated
| connection element for connection to an electrical circuit
| board.

Deleted: o
Deleted: (1)
Deleted: one of the preceding
Deleted: s
Deleted: (30)

10

14. (claim 18 amended)

15 | The optical connector, according claim 1,
| wherein the connector has an external electrical shielding

Deleted: o
Deleted: (1)
Deleted: to one of the
preceding
Deleted: s
Deleted: (2)

15. (claim 19 amended)

The optical connector, according to claim 14,
wherein the external electrical shielding penetrates the
connector housing.

16. (claim 20 amended)

The optical connector, according to claim 14,
wherein the shielding is designed in the form of an
essentially U-shaped clamp which engages around the
connector housing rearwards.

17. (claim 21 amended)

The optical connector, according to claim 16,
wherein the ESD protection means is arranged essentially
centrally in the U-shaped clamp.

18. (claim 22 amended)

The optical connector, according to claim 16,
wherein the clamp has integrally formed press-on lugs for
biasing the electro-optical components against the rear
wall of the housing in the introduction direction.

Deleted: o

Deleted: (1)

Deleted: 18

Deleted: (2)

Deleted: (40)

Deleted: o

Deleted: (1)

Deleted: 18 or 19

Deleted: (2)

Deleted: (4)

Deleted: o

Deleted: (1)

Deleted: 20

Deleted: (30)

Deleted: o

Deleted: (1)

Deleted: 20 or 21

Deleted: which are

Deleted: ed

Deleted: sid

Deleted: order to apply force
to the latter counter to

Deleted: (B)

Deleted: 23. Optical
connector (1), in
particular for establishing
multimedia-connections in a
motor vehicle according to
the MOST-standard and in
particular according one of
the preceding claims,
comprising:

...a dielectric connector
housing (40) with a
receptacle (50) for mating
connection with a
complementary connector, .
...at least an optical
connection element (94, 96)
in said connector housing
(40) and for mating
connection with a
complementary optical
connection

Deleted: element of the
complementary connector, .
...at least an electro-
optical component (54, 56)
with electronic circuits
and .

...at least an electrically
conductive protection

[7]

19. (claim 25 amended)

Use of a protection element, with an optical connector
designed for the MOST-standard, the optical connector
5 having a receptacle, in a connector housing, for mating
connection with a complementary connector and, having
optical connection elements, which are positioned in said
receptacle, wherein said protection element, is provided,
in the region of the optical connection elements, and
10 comprises at least one discharge section for each optical
connection element arranged in the vicinity thereof, each
extending towards said receptacle, and having free ends
being exposed to the interior of the receptacle, thereby
preventing an electrostatic discharge from an object which
15 is introduced into said receptacle, onto said optical
connection elements, within said connector,
wherein said protection element has electrically
conductive fingers which penetrate said connector housing.

Deleted: (30) against
electrostatic discharges

Deleted: (1), in particular
according to

Deleted: with

Deleted: (50)

Deleted: (40)

Deleted: with

Deleted: (94, 96)

Deleted: (30)

Deleted: in such a way

Deleted: (94, 96) that said
protection element

Deleted: s

Deleted: (50)

Deleted: (94, 96)

Deleted: